



CBRN Magyarország KFT

**AV**  
AeroVironment™



## telemax™ EVO HYBRID

The telemax EVO HYBRID is a versatile UGV designed to be operated by bomb technicians. It is ideally suited for operation in confined spaces (airplanes, underground trains and buses) featuring a strong 6-axis precision manipulator with Tool Center Point Control and automatic tool exchange. Its 4-track drive system with auto-leveling can easily handle multiple gradients, gaps and terrains. An expansive payload bay and automatic tool exchange allow operators to take multiple tools, disruptors or other sensors downrange, eliminating round-trip load-outs. Onboard IP Mesh radio delivers secure communications in complex urban environments and the HD pan-tilt-zoom camera produces razor-sharp images with four simultaneous video feeds (QuadView). All AeroVironment UGVs feature the intuitive and operationally simplified Robo Command Control Station with multi-touch screen, pre-programmed motion sequences and ergonomically designed hand controllers for precision control of the robot, manipulator and accessories.

# Compact and Powerful for Toughest Challenges

telex™ EVO HYBRID

## DISTINCTIONS



» LIFTING CAPACITY  
82 lb (37 kg)



» GRIPPER WIDTH  
8 in (200 mm)



» MISSION DURATION  
Up to 10 hr



» CLIMB STAIRS AND SLOPES  
45°

## SPECIFICATIONS

TOTAL PAYLOAD CAPACITY	68 lb (31 kg)
SPEED	Max. 6.2 mph (10 km/h)
DIMENSIONS	32 in x 16 in x 30 in (815 mm x 400 mm x 770 mm)
WEIGHT	Max. 176 lb (80 kg)
DRIVE MECHANISM	4-track running gear with individually adjustable flippers; optional wheels
FUNCTIONALITY	Obstacle Height: 20 in (500 mm) Gap Width: 24 in (600 mm)

Technical data ±5% tolerance

## INTERCHANGEABLE ACCESSORIES



Optics/Visual  
Augmentation



UGV  
Communications



Power  
Sources



Wheels/  
Tracks



Tooling &  
Hauling



Render Safe  
Options

## MISSION VARIANTS



EOD  
Explosive Ordnance  
Disposal



HAZMAT  
Hazardous  
Materials




CBRNE  
Chemical, biological,  
radiological, nuclear &  
explosives



SWAT  
High Risk Law  
Enforcement  
Operations

LIFT CAPACITY AT DISTANCE  
16.5 lb (7.5 kg) // 61 in (1560 mm)  
26 lb (12 kg) // 47 in (1200 mm)  
44 lb (20 kg) // 37 in (950 mm)  
82 lb (37 kg) // 24 in (600 mm)



### ROBO COMMAND

Interoperable controller,  
radio & communications—  
reducing operation,  
training & logistics



## KEY FEATURES

- » 6-axis precision manipulator
- » Tool Center Point Control—providing maximum movement flexibility of the manipulator
- » Fully integrated 2-way audio module
- » HD pan-tilt-zoom camera—displays four video feeds (QuadView)
- » Versatile 4-track drive system—handles gradients/obstacles/gaps
- » Easy access to pre-programmed manipulator & flipper motion sequences
- » IP Mesh Radio Network with optional repeaters provide secure & resilient communications over extended ranges

Magyarországon kizárólagosan forgalmazza:

**CBRN Magyarország Kft.**  
H-1097 Budapest, Illatos út 11/b.  
Tel./Fax: +36 1 280-6428  
[www.cbrnmagyarorszag.hu](http://www.cbrnmagyarorszag.hu)  
[info@cbrnmagyarorszag.hu](mailto:info@cbrnmagyarorszag.hu)

AeroVironment - ph: 805.520.8350 - [www.avinc.com](http://www.avinc.com) // © 2023 AeroVironment, its product names and the AV logo are protected trademarks of AeroVironment Inc. All other company, product names, logos, and brands are property of their respective owners and are for identification purposes only. Use of these names, logos, and brands does not imply endorsement. Screen images may be simulated. All specifications are subject to change. This data sheet consists of AeroVironment, Inc. general capabilities information that does not contain controlled technical data as defined within the International Traffic in Arms Regulations (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.

**AV**  
AeroVironment™